

(51) International Patent Classification 6 : H04B 7/005		A2	(11) International Publication Number: WO 00/01085
			(43) International Publication Date: 6 January 2000 (06.01.00)
(21) International Application Number: PCT/IB99/01087		(81) Designated States: JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 10 June 1999 (10.06.99)		Published	
(30) Priority Data: 09/107,546 30 June 1998 (30.06.98) US		Without international search report and to be republished upon receipt of that report.	
(71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).			
(71) Applicant (for SE only): PHILIPS AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE).			
(72) Inventor: GHOSH, Monisha; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).			
(74) Agent: SCHOENMAKER, Maarten; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).			

The diagram shows a digital filter structure. An input signal $n_k = \sum_{i=0}^{L_h-1} h_i \bar{a}_{k-i} + n_k$ enters a feedforward block 12 containing coefficients $h_0, h_1, h_2, \dots, h_{L_h-1}$. The output of block 12 is added at a summing junction 18 to the output of a feedback block 16. The feedback block 16 contains coefficients $b_1, b_2, \dots, b_{L_b-1}$ and receives the output \hat{a}_k of a delay block 14. The output of the summing junction 18 is \bar{a}_k , which is then processed by a delay block 14 to produce \hat{a}_k . Additionally, \bar{a}_k is fed into a block 22 containing coefficients $g_1, g_2, \dots, g_{L_g-1}$, which produces the final output $y_k = \bar{a}_k + \sum_{i=1}^{L_g-1} g_i \bar{a}_{k-i}$.

A method and device for improving DFE performance in a trellis coded system by placing a short adaptive predictive filter after the DFE in order to whiten the error sequence at the output of the DFE.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Method and device for improving DFE performance in a trellis-coded system.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention is directed in general to digital signal processing, and in particular to receiver based methods and devices for improving decision feedback equalizer ("DFE") performance in a trellis coded system.

2. Background of the Invention

In many digital communication scenarios (e.g. telephone transmission, broadcast TV transmission, cable etc.) The transmitted signal arrives at the receiver through more than one path in addition to the direct path. This condition is called "multipath" and leads to intersymbol interference ("ISI") in the digital symbol stream. This ISI is compensated for in the receiver through an equalizer which in many cases is a DFE as shown in Fig. 1. U.S. Patent No. 5,572,262 shows one method of combating these multipaths.

A DFE 10 (Fig. 1) has two filter sections, a forward filter 12 and a feedback filter 16. The input to the forward filter 12 is the received data which includes the transmitted symbol sequence a_k , noise n_k and multipath h_i . The input to the feedback filter 16 is the quantized equalizer output \hat{a}_k . The output of both the sections are summed 18 to form the final equalizer output \tilde{a}_k which is also the input to the next stage in a trellis-coded system, the trellis decoder. While a DFE performs better than a linear equalizer in severe ISI, the performance is limited by error propagation through the feedback filter 16 of the DFE 10. Error propagation occurs in the feedback filter 16 when the quantized equalizer output \hat{a}_k is not the same as the transmitted symbol a_k . If an error is made in determining the symbol \hat{a}_k at the output of the slicer 11, this incorrect symbol is fed back to the input of the feedback filter 16 and propagates. In many systems which employ error correction codes like trellis codes and/or Reed-Solomon codes to obtain very low error rates at moderate SNRs, the "raw" symbol error rate (SER) at the equalizer output can be extremely high. For example, in the VSB system, at threshold in white noise the SER at the equalizer output is about 0.2. The increased error propagation due to these high SERs can cause the DFE to lose a couple of dB in performance as compared to the case of no error propagation. Additionally, the error propagation causes

the error sequence at the equalizer output to be correlated, since it depends on past incorrect symbol decisions. This correlation has an adverse effect on the subsequent trellis decoder which is usually designed for a white noise sequence.

5 SUMMARY OF THE INVENTION

Accordingly, it is an object of the invention to reduce the mean-squared-error (MSE) and correlation of the DFE output error sequence. This object is achieved by placing a short adaptive predictor filter after the DFE in order to whiten the error sequence. The ISI introduced into the data symbol stream by this filter is then compensated in the trellis decoder
10 by the use of delayed decision feedback sequence estimation (DDFSE) as described in "Delayed decision-feedback sequence estimation," by A. Duel-Hallen and C. Heegard, IEEE Trans. Commun., vol. COM-37, no. 5, pp. 428-436, May 1989.

The invention has applications in any trellis coded system that utilizes a DFE for equalization, especially in cases where the SER after the equalizer is high and error
15 propagation causes problems. An example is terrestrial transmission of digital TV signals.

The invention can also be used in trellis coded systems with DFEs which are subject to colored noise interference. Again, the DFE cancels much of the interference but the adaptive predictor serves to whiten the noise further. This helps improve the trellis decoder performance.

20 The invention accordingly comprises the several steps and the relation of one or more of such steps with respect to each of the others, and the apparatus embodying features of construction, combinations of elements and arrangement of parts which are adapted to effect such steps, all as exemplified in the following detailed disclosure, and the scope of the invention will be indicated in the claims.

25

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the invention reference will be had to the following drawings:

- Figure 1 shows a standard DFE;
30 Figure 2 shows a DFE in accordance with the invention; and
Figure 3 shows a DFE in accordance with the invention during a training sequence.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Figure 1 is a diagram of the standard decision feedback equalizer 10 (DFE).

The DFE includes a forward filter 12, a slicer 14, a feedback filter 16 and a subtractor 18. Let a_k be the transmitted trellis-coded symbol stream. The received signal r_k after multi-path distortion and added noise n_k can be written as

$$r_k = \sum_{i=0}^{L_h-1} h_i a_{k-d_h-i} + n_k \quad (1)$$

where $h_i, i=0 \dots L_h-1$ is the multipath channel of length l_h and delay d_h , and n_k is the additive noise which in general is neither gaussian nor white. The forward filter 12 is used to remove the pre echo or ghosts in the received signal. The slicer 14 quantizes the signal \tilde{a} to the nearest symbol \hat{a}_k . If an error is made in this quantization the error is passed to the feedback filter 16 and remains in the system. The output of the feedback filter 16 is subtracted from the output of the forward filter 12 to provide \tilde{a}_k . \tilde{a}_k is an estimate of the transmitted symbol a_k plus, an error e_k . It can also be expressed as:

$$\tilde{a}_k = \sum_{i=0}^{L_f-1} f_i r_{k+d_f-i} + \sum_{i=1}^{L_b} b_i \tilde{e}_{k-d_b-i} \quad (2)$$

where $f_i, i=0 \dots L_f-1$ are the forward equalizer taps, $b_i, i=1 \dots L_b$ are the feedback taps, d_f is the delay through the forward equalizer, d_b is the delay in the feedback equalizer and \tilde{a}_k is the constellation point closet to \tilde{a}_k . In the absence of error propagation, i.e. if $\hat{a}_k = a_k$, the error sequence e_k at the equalizer output 20 is white. However, in most cases the error propagation causes this error sequence to be correlated, that is, the noise samples are no longer independent. The "colored" noise affects the performance of a trellis coder, because a trellis coder is optimized for performance in a channel having all white gaussian noise.

In accordance with the invention, as shown in Fig. 2, an adaptive filter 22 is placed at the output of the DFE 10 but before a trellis decoder (not shown). The output of filter 22 can be expressed as

$$y_k = \tilde{a}_k + \sum_{i=1}^{L_g} g_i \tilde{a}_{k-i} \quad (3)$$

where $(1, g_1, g_2, g_3 \dots g_{L_g})$ are the taps of the adaptive filter. Since $\tilde{a}_k = a_k + e_k$, then the adaptive filter output can be written as

$$\begin{aligned} y_k &= a_k + \sum_{i=1}^{L_g} g_i a_{k+i} + e_k + \sum_{i=1}^{L_g} g_i e_{k-i} \\ &= a_k + \sum_{i=1}^{L_g} g_i a_{k+i} + e'_k \end{aligned} \quad (4)$$

If the filter taps are chosen so as to minimize the variance of e'_k , the SNR of the sequence y_k can be improved. In addition, since e'_k is the prediction error sequence of the equalizer output error sequence e_k , it will be white see Widrow and Stearns, "Adaptive Signal Processing," (hereby incorporated by reference), at pages 99-116), which does not affect the performance of a trellis decoder.

Training of the Adaptive Filter

To minimize the error from the output of the DFE, or in other words to tune the adaptive filter taps g to the error e_k , the adaptive filter 22 is first placed through a training sequence as shown in Fig. 3. In many applications, such as digital TV, the training sequence is part of the transmitted signal. After the equalizer 10 has converged (via blind means, without using the signal a_k , or trained means which uses the signal a_k) the adaptive filter 22 receives a training sequence which is the difference between the output of the DFE \tilde{a}_k and the transmitted symbol sequence a_k . This difference is the error e_k produced by the DFE.

$$\tilde{a} - a_k = e_k \quad (5)$$

This error sequence e_k is then input into the adaptive filter 22. The adaptive filter 22 forms an output sequence x_k as shown in Fig. 3, where

$$x_k = e_k + \sum_{i=1}^{L_g} g_i e_{k-i} \quad (6)$$

The filter taps g_k are adapted using the LMS algorithm as follows

$$\underline{g}(k+1) = \underline{g}(k) - \mu x_k \underline{e}(k) \quad (7)$$

where $\underline{g} = [g_1, g_2, \dots, g_{L_g}]$ and $\underline{e}(k) = [e_k, e_{k-1}, e_{k-2}, \dots, e_{k-L_g}]$. This adaptation adapts the filter taps to minimize the mean squared, error e_k^2 , of the DFE.

Since the trellis decoder uses the taps $[g_1, g_2, \dots, g_{L_g}]$ in a feedback loop, error propagation can also occur hence it is also beneficial to limit the size of the taps g during adaptation, so that the trellis decoder that uses these taps does not suffer error propagation. If g is too small, however, the efficiency of the adaptive filter is reduced. Accordingly, an additional power constraint is imposed on the LMS algorithm to limit the amplitude of the taps which reduces the error propagation in the DDFSE trellis decoder (described next). A parameter P is chosen such that it is required that

$$\sum_{i=1}^{L_g} g_i^2 \leq P \quad (8)$$

At each step of the LMS algorithm this condition is tested, and if violated, the taps are rescaled appropriately.

The Adaptive Filter and DDFSE

- 5 Once the adaptive filter 22 is appropriately trained to minimize e_k , $\tilde{a}_k = a_k + e_k$ is input to the adaptive filter 22. The adaptive filter 22 although it has been trained to minimize e_k , it will also distort \tilde{a}_k . Equation 9 shows this distortion and represents the output of adaptive filter 22 as follows:

$$y_k = a_k + \sum_{i=1}^{L_g} g_i a_{k-i} \quad (9)$$

- 10 As stated above, if the filter taps g are chosen to minimize e_k , the SNR of the sequence y_k can be improved. y_k , however, is a distorted \tilde{a}_k and includes the ISI introduced into the data stream by the adaptive filter 22. This distortion is then compensated for in the trellis decoder by use of delayed decision feedback sequence estimation (DDFSE) as described in A. Duel-Hallen and C. Heegard, "Delayed decision-feedback Sequence Estimation," IEEE Trans. Common., Vol. Com - 37, no. 5, pp. 428-436, May 1989, hereby incorporated by reference, and as summarized below.

From the definition of y_k , we see that an optimum trellis decoder which will remove the distortion of \tilde{a}_k , should minimize the metric (maximum likelihood decoding):

$$\sum_k \left[y_k - a_k - \sum_{i=1}^{L_g} g_i a_{k-i} \right]^2 \quad (10)$$

- 20 This equation, however, requires past symbol sequences a_{k-i} to be saved, and each tap g_i in the adaptive filter therefore introduces more memory into the system which causes the number of steps of a trellis decoder to grow exponentially with the number of taps in the adaptive filter 22. Therefore an expanded trellis is necessary to accommodate the memory (a_{k-i}) introduced by the adaptive filter 22.

- 25 A suboptimum, but computationally less intensive way of performing the trellis decoding is to instead minimize the following metric:

$$\sum_k \left[y_k - a_k - \sum_{i=1}^{L_g} g_i \hat{E}_{k-i,j} \right]^2 \quad (11)$$

- where the sequence $\hat{a}_{k-i,j}$, $i=1, \dots, L_g$ is the survivor symbol sequence associated with state j in the trellis. This scheme does not expand the number of states in the original trellis, but instead
30 introduces decision-feedback in each of the trellis states. That is, since this scheme uses \hat{a}_{k-i} ,

which is merely an estimate of, rather than the actual value a_{k-i} , there is no memory introduced into the system. Since there is no memory, an expanded trellis is not required, i.e. the number of states in the trellis remains the same even with the additional adaptive filter 22.

5 There is the possibility of error propagation in this implementation and hence the precaution is taken in the LMS algorithm of limiting the amplitude of the filter taps. The optimum value of P will depend on the trellis code and application. In the United States HDTV example, simulation results indicate that a value of $P=0.15$ gives good performance.

10 It will thus be seen that the objects set forth above, among those made apparent from the preceding description, are efficiently attained and, since certain changes may be made in carrying out the above method and in the construction set forth without departing from the spirit and scope of the invention, it is intended that all matter contained in the above description and shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

CLAIMS:

1. A decision feedback equalizer, (DFE) comprising:
an input which receives an input signal comprising, a transmitted symbol stream, noise and multipath;
5 a DFE output which provides a DFE output signal (\hat{a}_k);
a forward filter (12) which filters the input signal;
a decision feedback loop comprising a subtractor (18), a slicer (14), and a feedback filter (16), wherein the subtractor (18) is coupled to both an output of the forward filter (12) and an output of the feedback filter (16) and subtracts the output of the feedback
10 filter (16) from the output of the forward filter (12) to provide the DFE output signal (\hat{a}_k) which is applied to an input of the slicer (14); and
an adaptive filter (22), coupled to the DFE output, to adaptively filter the DFE output, and whiten an error in the DFE output signal.
- 15 2. The DFE as claimed in claim 1, further including a training device which trains the adaptive filter to minimize the mean squared error in the DFE output.
3. A device for improving DFE performance, comprising:
an input which receives an output of a DFE;
20 an adaptive filter (22) having an adaptive filter input and an adaptive filter output, the adaptive filter input coupled to the input; and
an output coupled to the adaptive filter output for supplying an output signal to a DDFSE trellis decoder, which output signal is the DFE output signal with a smaller whiter error than the error in the output of the DFE.
- 25 4. The device as claimed in claim 3, wherein the adaptive filter (22) is adapted to receive a training sequence that adapts filter taps ($g_1 \dots g_{L-1}$) in the adaptive filter such that the adaptive filter (22) acts to whiten the error in the output of the DFE (\hat{a}_k).

5. The device as claimed in claim 4, wherein the adaptive filter (22) further includes a LMS algorithm which is used to adapt the filter taps.

6. The device as claimed in claim 5, wherein the adaptive filter further includes a
5 device for comparing

$$\sum_{i=1}^{L_f} g_i^2 \leq P \quad (11a)$$

where g_i is a filter tap and P is a power constraint imposed on the LMS algorithm to limit
10 amplitude of the filter taps.

7. A method of improving DFE performance, comprising the steps of:
receiving an output signal from the DFE which includes

$\tilde{a}_k + e_k$;

15 adaptively filtering $\tilde{a}_k + e_k$;
providing the adaptively filtered $\tilde{a}_k + e_k$ to a DDFSE.

8. A method of decision feedback equalizing, comprising the steps of:
receiving an input signal comprising a plurality of symbols, noise and

20 multipath;

forward filtering the received signal using a forward filter having a plurality of
taps;

subtracting from the forward filtered signal a feedback filtered signal to provide
a decision feedback output;

25 quantizing the decision feedback output to the nearest symbol to provide a
quantized output;

feedback filtering the quantized output to provide the feedback-filtered signal;

and

adaptively filtering the decision feedback output.

30

9. A DFE, comprising:

a forward filter (12), having an input which receives an input signal and a
forward filter output;

a subtractor (18) having a first input coupled to the forward filter output and having a second input and a subtractor output;

a slicer (14) having an input coupled to the output of the subtractor and a slicer output;

5 a feedback filter (16) coupled to the slicer output and the second input of the subtractor; and

an adaptive filter (22) coupled to the output of the subtractor.

10. A television receiver, including a DFE, comprising:

10 a forward filter (12), having an input for receiving an input signal and a forward filter output;

a subtractor (18) having a first input coupled to the forward filter output and having a second input and a subtractor output;

15 a slicer (14) having an input coupled to the output of the subtractor and a slicer output;

a feedback filter (16) coupled to the slicer output and the second input of the subtractor;

an adaptive filter (22) having an input coupled to the output of the subtractor and an adaptive filter output; and

20 a DDFSE having an input coupled to an output of the adaptive filter.

11. A device for improving DFE performance, comprising:

DFE means (12,18,14,16) having an input and an output for providing a DFE output signal; and

25 adaptive filter means (22) coupled to the output of the DFE for adaptively filtering the DFE output signal and thereby whitening noise in the DFE output signal.

1/3




FIG. 1

2/3




FIG. 2

3/3





FIG. 3



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H04B 7/005, H04L 27/01	A3	(11) International Publication Number: WO 00/01085
		(43) International Publication Date: 6 January 2000 (06:01:00)
<p>(21) International Application Number: PCT/IB99/01087</p> <p>(22) International Filing Date: 10 June 1999 (10.06.99)</p> <p>(30) Priority Data: 09/107,546 30 June 1998 (30.06.98) US</p> <p>(71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).</p> <p>(71) Applicant (for SE only): PHILIPS AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE).</p> <p>(72) Inventor: GHOSH, Monisha; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).</p> <p>(74) Agent: SCHOENMAKER, Maarten; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).</p>		<p>(81) Designated States: JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report.</p> <p>(88) Date of publication of the international search report: 30 March 2000 (30.03.00)</p>

(54) Title: METHOD AND DEVICE FOR IMPROVING DFE PERFORMANCE IN A TRELLIS-CODED SYSTEM



(57) Abstract

A method and device for improving DFE performance in a trellis coded system by placing a short adaptive predictive filter after the DFE in order to whiten the error sequence at the output of the DFE.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 99/01087

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: H04B 7/005, H04L 27/01

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H04B, H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5742642 A (ANTONI FERTNER), 21 April 1998 (21.04.98), abstract --	1-11
A	EP 0707401 A2 (WANG, JIN-DER), 17 April 1996 (17.04.96), figures 2-3 --	1-11
A	US 5249200 A (MICHAEL CHEN ET AL), 28 Sept 1993 (28.09.93), column 7, line 64 - line 68; column 8, line 1 - line 5, figures 1,2C --	1-11
A	US 5909466 A (JOËL LABAT ET AL), 1 June 1999 (01.06.99), abstract --	1-11



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"F" document member of the same patent family

Date of the actual completion of the international search

24 January 2000

Date of mailing of the international search report

29-01-2000

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Rune Bengtsson/MN

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 99/01087

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5809086 A (SIRIKIAT ARIYAVISITAKUL), 15 Sept 1998 (15.09.98), abstract -----	1-11

INTERNATIONAL SEARCH REPORT
Information on patent family members

02/12/99

International application No.

PCT/IB 99/01087

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5742642 A	21/04/98	AU 4889397 A WO 9819432 A	22/05/98 07/05/98
EP 0707401 A2	17/04/96	CA 2158185 A CN 1123978 A IL 115588 A JP 8274724 A US 5604769 A	14/04/96 05/06/96 17/08/99 18/10/96 18/02/97
US 5249200 A	28/09/93	EP 0596904 A WO 9303554 A	18/05/94 18/02/93
US 5909466 A	01/06/99	CN 1196147 A EP 0850527 A FR 2738967 A,B WO 9710664 A FR 2744481 A	14/10/98 01/07/98 21/03/97 20/03/97 08/08/97
US 5809086 A	15/09/98	NONE	

This Page Blank (uspto)